

USB-C Travel Dock with Power Pass-Through


UH3238

Designed and made to be a portable and versatile connectivity solution, the UH3238 USB-C Travel Dock with Power Pass-Through contains 5 essential ports — one audio port, two USB Type-A ports, one HDMI port, and one USB-C DC in port — to provide connectivity and power supply for users that travel and require mobile office scenarios. The Thunderbolt™ 3 and USB 3.2 Gen 1- compatible interface guarantees superior data transmission speed up to 5 Gbps. With the support for up to 4K HDMI (3840 x 2160 @ 60Hz), the device allows users to multitask at stunningly realistic UHD resolution. The UH3238 boasts a plug-and-play design and is compatible with all major operating systems (Windows®, macOS X, iPadOS, and Android). Weighing at just 44g, it is a compact, yet competent, and ideal data and power transmission solution for every mobile workstation ecosystem.



Features

- 5-in-1 travel dock that includes one audio port, two USB Type-A ports, one HDMI port, and one USB-C DC in port
- Supports USB PD 3.0 for charging up to 92W via USB-C PD power adapter — power profiles include 5V, 9V, 15V, 20V
- Supports DP 1.4 Alt mode with up to 4K (3840 x 2160) @ 60Hz for superior video output
- Plug and Play — no drivers needed
- Works with all major operating systems: Windows®, macOS X, iPad Pro (USB-C), and Android
- Compatible with Thunderbolt™ 3 (USB-C)
- Compact, lightweight design for mobile workstation



Support

5V
 9V
 15V
 20V

Check USB-C charge rate of your laptop*
 The total charging time may vary depending on the devices connected to the UH3238.
 *USB-C PD power adapter is not included in the package.

Specifications

UH3238	
Computer Connections	1
Connectors	
Computer	USB 3.2 Gen 1 Type-C
Device	2 x USB 3.2 Gen 1 Type-A Female (Blue)* 1 x USB 3.2 Gen 1 Type-C Female (Black)* *a. 1 x USB 3.2 Gen 1 Type-A supports BC 1.2 (5V, 7.5W) *b. 1 x USB 3.2 Gen 1 Type-A supports 5V, 4.5W *c. The total output of 2 x USB-A ports is max. 5V, 9W *d. 1 x USB 3.2 Gen 1 Type-C supports 5V, 7.5W *e. The total output of 3 x USB (2A+1C) ports is max. 5V, 7.5W
Video Output	1 x HDMI Female (Black)
Audio	1 x 3.5mm stereo 4-pole microphone and headphone jack
Power	1 x USB-C Female (supports USB 3.2 Gen 1 Data transfer)* *Supports PD 3.0 for laptop charging up to 92W. Power profiles include 5V, 9V, 15V, 20V (additional USB-C PD power adapter needed)
Video Resolution	3840 x 2160 @ 60Hz* *To get max. bandwidth, upstream should support standard DP1.4 Alt mode with DSC3:1 and HBR3. When connecting a DP1.2 Alt mode supported upstream, the max. resolution of HDMI is 4K @ 30Hz due to bandwidth limitation
Power Consumption	5V, 8W
System Requirements	Windows® 10 or later, USB-C enabled computer with DP Alt Mode* *With Intel 7 th -Generation Core Processor (Kaby-Lake) and above. More info about CPU generation, please find: https://www.intel.com/content/www/us/en/processors/processor-numbers.html macOS X 10.12 or later, USB-C enabled computer iPadOS 13.1 or later, iPad Pro (USB-C) Android 8.0 or later, USB-C enabled Smartphone with DP Alt Mode
Environmental	
Operating Temperature	0 – 40°C
Storage Temperature	-20 – 60°C
Humidity	0 – 80% RH, Non-condensing
Physical Properties	
Housing	Aluminum
Weight	44 g
Dimensions (L x W x H)	9.00 x 3.20 x 0.82 cm

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Product information is subject to change without prior notice.

Released: 07/2021 V1.0

© Copyright 2021 ATEN® International Co. Ltd.
 ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.
 The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

